



Data Sheet

DESCRIPTION

ResinDriveways resin is a clear, UV stable Polyurethane. It is used to bind a blend of natural aggregates with a measured amount of good quality clear sand to give an attractive and durable surface with good cracking resistance.

Suitable bases include Concrete and Asphalt. Areas to be dressed should be clean, dry and strong enough to take anticipated loadings.

For further surface preparation details refer to the Preparation and Application Data Sheet.

APPLICATION COVERAGE RATES

When mixed with the correct ratios of resin to aggregate, the application rates per unit are as follows:

Depth	Coverage
15mm	4.0m ²
18mm	3.3m ²
21mm	2.9m ²

Please be aware that coverage rates of some of our Premium Range finishes will vary from the above rates.

COLOUR

ResinDriveways Part A is a honey coloured liquid.
ResinDriveways Part B is a clear liquid.

POT LIFE

The shelf life of unopened ResinDriveways Part A is 24 months if stored above 5°C and not in direct sunlight.

The shelf life of unopened ResinDriveways Part B is 6 months if stored above 5°C and not in direct sunlight.





CURING TIME

Curing times are influenced by site conditions, particularly the ambient temperature during installation and the quantity of catalyst added to the mix. The times below are provided as a general guide under normal conditions:

Typical cure time at 15°C for pedestrian use: Approximately 6 hours

Typical cure time at 15°C before vehicle traffic: Approximately 24 hours

Please note that cooler temperatures may extend curing times, while warmer conditions can reduce them.

TEMPERATURE OF APPLICATION

Recommended temperature of application is between 5°C and 25°C.

Accelerators can be used to speed up cure times in a variety of situations. Please consult us for further advice should this be of interest.

PACKAGING

ResinDriveways resin is supplied in two containers. Part 'A' (Resin) and Part 'B' (Curing Agent).

CLEANING OF TOOLS AND HANDS

Tools, machinery etc, should be cleaned immediately after use with Xylene or our **RESIN CLEANER**. **NOT WHITE SPIRIT**. Avoid contact with skin and use organic hand cleaner on hands.

No naked flames should be used with Xylene.

HEALTH & SAFETY PRECAUTIONS

Before using these products please ensure you have been supplied and have read carefully the following:

1. Data sheet and method statement
2. Material Safety Data Sheet.

Any guidance, recommendations, or technical information provided by ResinDriveways.co.uk is offered in good faith and is based on the company's experience and knowledge at the time it is published. While every effort is made to ensure the accuracy of the information, ResinDriveways.co.uk, its employees, representatives, and agents accept no responsibility or liability, including liability arising from negligence, for any loss or damage resulting from its use.

Any performance figures, measurements, or data provided are intended as typical reference values only and should not be interpreted as a guaranteed product specification.

