



DATA SHEET

DESCRIPTION

This UV-resistant, clear polyurethane resin is designed for use in resin-bound paving systems. When combined with carefully graded natural aggregates, it creates a durable, visually appealing surface that offers excellent long-term performance and resistance to cracking under normal conditions.

The resin can be applied to suitably prepared concrete or asphalt substrates. Before installation, the base must be structurally sound, clean, dry, and capable of supporting the expected loads. Any existing movement or cracks within the substrate may transfer through to the finished resin-bound surface over time.

For detailed guidance on substrate preparation and installation procedures, please refer to the relevant Surface Preparation and Application Guide.

APPLICATION COVERAGE RATES

Depth	Coverage
15mm	4.0m ²
18mm	3.3m ²
21mm	2.9m ²

Please be aware that coverage rates of some of our Premium Range finishes will vary from the above rates.

COLOUR

Resin Driveways Resin Part A is a yellow liquid
Resin Driveways Resin Part B is a clear liquid.

POT LIFE

The shelf life of unmixed Part A is 24 months if stored above 5°C.

The shelf life of unmixed Part B is 6 months if stored above 5°C.

CURING TIME

The curing times will vary depending on the temperature at the time of application, and any additional catalyst used. Typical cure times are as follows: Full chemical cure 24 hours. Allow 48 hours before vehicle access.

TEMPERATURE OF APPLICATION

Recommended temperature of application is between 5°C and 25°C.

Accelerators can be used to speed up cure times in a variety of situations. Please consult us for further advice should this be of interest.

PACKAGING

Resin Driveways resin is supplied in two containers. Part 'A' (Resin) and Part 'B' (Curing Agent).

CLEANING OF TOOLS AND HANDS

Tools, machinery etc, should be cleaned immediately after use with Xylene or our **RESIN CLEANER. NOT WHITE SPIRIT.** Avoid contact with skin and use organic hand cleaner on hands.

No naked flames should be used with Xylene

HEALTH & SAFETY PRECAUTIONS

Before using these products please ensure you have been supplied and have read carefully the following:

1. Data sheet and method statement
2. Material Safety Data Sheet.

Any guidance, recommendations, or technical information provided by ResinDriveways.co.uk is offered in good faith and is based on the company's experience and knowledge at the time it is published. While every effort is made to ensure the accuracy of the information, ResinDriveways.co.uk, its employees, representatives, and agents accept no responsibility or liability, including liability arising from negligence, for any loss or damage resulting from its use.

Any performance figures, measurements, or data provided are intended as typical reference values only and should not be interpreted as a guaranteed product specification.

